

MATERIAL SAFETY DATA SHEET

FUTURE TOOLS INC.
13591 CABLE RD PATASKALA OH 43062
PRODUCT NAME : SLIKSTYX
24 HOUR EMERGENCY PHONE NUMBER : 866-860-4962

SECTION ONE HAZARDOUS INGREDIENTS

MATERIALS	CAS REG. NO.	TLV / UNITS	SOURCE	%
Hydrocarbon Propellant	68-476-86	N/A		10-30
Mineral Oil	8042-47-5	PPM	OSHA	10-30
Petrolatum	8009-03-08	PPM	OSHA	10-30
Isoparrifinic	64742-47-8	PPM	OSHA	10-30

SECTION TWO PHYSICAL PROPERTIES

APPEARANCE AND ODOR : Yellow Spray with slight odor

SPECIFIC GRAVITY (H₂O = 1) @ 25 °C NA

BOILING POINT °F (°C) : NA VAPOR PRESSURE (mm of Hg) ND

FREEZING POINT °F (°C) : NA % VOLATILES BY VOLUME : 30+%

EVAPORATION RATE : <1 (WATER =1) VISCOSITY SUS @ 100 °F : N / A

pH AS IS :NA APPROX. HEATING COEFFICIENT : N / A

VAPOR DENSITY (AIR = 1) : >1

SECTION THREE FIRE AND EXPLOSIVE HAZARDS

FLASH POINT : Aerosol :Extremely Flammable FLAMMABLE LIMITS : LEL / UEL - N / A

METHOD USED : Flame Extension AUTO IGNITION TEMP. : N / D

EXTINGUISHING MEDIA : DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER.

SPECIAL FIRE FIGHTING PROCEDURES : Beware of cans exploding

UNUSUAL FIRE AND EXPLOSION HAZARDS : NONE KNOWN

OTHER SPECIAL HAZARDS : NONE KNOWN

SECTION FOUR REACTIVITY DATA

STABILITY : STABLE

PRODUCT NAME : SLIKSTYX

CONDITIONS TO AVOID : NONE KNOWN

INCOMPATIBILITIES : NONE KNOWN

HAZARDOUS DECOMPOSITION : NONE KNOWN

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR.

SECTION FIVE HEALTH HAZARD SUMMARY

EYES : CAN CAUSE IRRITATION

SKIN CONTACT : MAY CAUSE FROST BITE

INHALATION : OIL MIST COULD COAT LUNGS

INGESTION :

THRESHOLD LIMIT VALUE : SEE SECTION ONE

MEDICAL CONDITION AGGRAVATED : NONE KNOWN.

KNOWN OR SUSPECTED CARCINOGEN : NTP / NIOSH SUSPECTED CARCINOGEN : NONE

SECTION SIX RECOMMENDED FIRST AID TREATMENT

EYES : FLUSH WITH WATER FOR AT LEAST 15 MINUTES, CONTACT PHYSICIAN.

SKIN : WASH WITH SOAP AND WATER.

INHALATION : MOVE TO FRESH AIR. RESUSCITATE IF NECESSARY. CONTACT PHYSICIAN.

INGESTION : DO NOT INDUCE VOMITING

SECTION SEVEN SPECIAL PROTECTION INFORMATION

GENERAL VENTILATION : NONE IN NORMAL USE.

LOCAL EXHAUST : NONE IN NORMAL USE

RESPIRATION PROTECTION : NONE IN NORMAL USE

MECHANICAL : NONE IN NORMAL USE

GLOVES : NONE IN NORMAL USE

EYE PROTECTION : USE SAFETY GLASSES OR GOGGLES.

PAGE 3 OF 3

**FUTURE TOOLS INC.
MATERIAL SAFETY DATA SHEET
PRODUCT NAME : SLIKSTYX**

OTHER : N / A

SECTION EIGHT SPILL OR LEAK PROCEDURES

CONTAINMENT PROCEDURES : CONTAIN SPILL WITH ABSORBENT AND TRANSFER TO PROPER CONTAINER.

PROTECTIVE CLOTHING : N / A

WASTE DISPOSAL PROCEDURES : DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION NINE STORAGE AND HANDLING REQUIREMENTS

HMS CODE: HEALTH 0, FLAMMABILITY 2, REACTIVITY 0.

HANDLING PROCEDURES : KEEP OUT OF CHILDREN'S REACH.

NOTE : THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING ACCURACY OF THE DATA OR RESULTS TO BE OBTAINED FROM THE USE THEREOF. IT IS USER'S OBLIGATION TO DETERMINE CONDITIONS OF SAFE USE OF THE PRODUCT AND WE ASSUME NO RESPONSIBILITY FOR ITS USE.

REVISION DATE : 1-1-2010

END MSDS.